



## BFK Liquid Line Bi-Directional Filter Drier

Description	Connection	Flow Capacity Tons @ 1 psi $\Delta P$ <sup>1,4</sup> (For kW, multiply tons by 3.5)			Water Capacity <sup>2</sup> Drops Of Water <sup>3</sup>					
					R-22		R-407C		R-410A	
		R-22	R-410A	R-407C	75°F	125°F	75°F	125°F	75°F	125°F
BFK-05 2	1/4 SAE	1.6	1.6	1.6	73	66	58	42	39	35
BFK-05 2S	1/4 ODF	2.2	2.2	2.2						
BFK-05 3	3/8 SAE	3.5	3.5	3.4						
BFK-05 3S	3/8 ODF	4.0	4.0	3.9	159	144	106	79	85	75
BFK-08 3	3/8 SAE	4.5	4.5	4.4						
BFK-08 3S	3/8 ODF	5.1	5.1	5.0						
BFK-08 4	1/2 SAE	6.4	6.4	6.3						
BFK-08 4S	1/2 ODF	6.7	6.7	6.6						
BFK-08 5	5/8 SAE	7.2	7.2	7.0						
BFK-08 5S	5/8 ODF	8.1	8.1	7.9	323	294	237	179	178	160
BFK-16 3	3/8 SAE	4.6	4.6	4.5						
BFK-16 3S	3/8 ODF	5.2	5.2	5.1						
BFK-16 4	1/2 SAE	7.7	7.7	7.6						
BFK-16 4S	1/2 ODF	8.1	8.1	7.9						
BFK-16 5	5/8 SAE	8.3	8.3	8.1	585	532	452	345	415	293
BFK-16 5S	5/8 ODF	8.7	8.7	8.5						
BFK-30 3S	3/8 ODF	5.8	5.8	5.7						
BFK-30 4	1/2 SAE	7.6	7.6	7.5						
BFK-30 4S	1/2 ODF	9.7	9.7	9.5						
BFK-30 5	5/8 SAE	10.3	10.3	10.1						
BFK-30 5S	5/8 ODF	14.2	14.2	13.9						
BFK-30 6S	3/4 ODF	16.0	16.0	15.7						
BFK-30 7S	7/8 ODF	16.7	16.7	16.4						
BFK-30 9S	1 1/8 ODF	18.0	18.0	17.5						

<sup>1</sup> All ratings in accordance with ARI Standard 710-04. 86°F liquid refrigerant temperature  
5°F saturated vapor temperature  
3.1 lbs./min./ton for R-134a  
2.9 lbs./min./ton for R-22 and R-407C  
4.0 lbs./min./ton for R-404A/507 and R-12  
2.7 lbs./min./ton for R-410A

<sup>2</sup> Water Capacities are based on:  
Equilibrium Point Dryness (EPD) of:  
50 parts per million for R-134a, R404-A/507,  
R-410A and R-407C  
60 parts per million for R-22  
15 parts per million for R-12

<sup>3</sup> 20 drops of water = 1 gram = 1 cc

<sup>4</sup> For 2 PSI  $\Delta P$ , Multiply values by 1.4

## Liquid Refrigerant Holding Capacity-Ounces

Unit Size	R-22		R-407C		R-410A	
	75°F	125°F	75°F	125°F	75°F	125°F
05	4.6	4.2	4.4	3.9	4.1	3.5
08	7.7	6.9	7.3	6.4	6.9	5.8
16	14.2	12.7	13.5	11.8	12.6	10.6
30	21.0	18.7	20.0	17.4	19.6	16.5