



**EMERSON**  
Climate Technologies

Datos de Rendimiento de Herméticos Para Aire Acondicionado - R-22 - 50 Hz - KCAL

| Modelo                | Monofásico |                 |                  |     | Trifásico |                 |                   |     |
|-----------------------|------------|-----------------|------------------|-----|-----------|-----------------|-------------------|-----|
|                       | KCAL       | VATIOS DE MOTOR | PFJ/T/Z AMPERIOS | EER | KCAL      | VATIOS DE MOTOR | TF5/D(M) AMPERIOS | EER |
| <b>HERMÉTICO R-22</b> |            |                 |                  |     |           |                 |                   |     |
| CR16K6                | 3,402      | 1,320           | 6                | 10  |           |                 |                   |     |
| CR18KQ                | 3,780      | 1,570           | 7                | 10  | 3,780     | 1,560           | 5.8/2.9           | 10  |
| CR18K6                | 3,704      | 1,440           | 7                | 10  |           |                 |                   |     |
| CR20KQ                | 4,082      | 1,660           | 7                | 10  |           |                 |                   |     |
| CR22K6                | 4,662      | 1,790           | 8                | 10  | 4,662     | 1,800           | 6.2/3.1           | 10  |
| CR24KQ                | 5,040      | 1,980           | 9                | 10  | 5,040     | 2,000           | 7.1/3.6           | 10  |
| CR24K6                | 5,065      | 1,860           | 9                | 11  | 5,065     | 1,860           | 6.8/3.5           | 11  |
| CR28KQ                | 5,695      | 2,350           | 12               | 10  | 5,695     | 2,350           | 8.5/4.2           | 10  |
| CR28K6                | 5,846      | 2,150           | 11               | 11  | 5,846     | 2,150           | 8.2/4.1           | 11  |
| CR30KQ                | 6,149      | 2,510           | 12               | 10  | 6,149     | 2,510           | --/4.4            | 10  |
| CR30K6                | 6,174      | 2,260           | 11               | 11  | 6,174     | 2,250           | 8.6/4.3           | 11  |
| CR32KQ                | 6,653      | 2,720           | 14               | 10  | 6,653     | 2,710           | 9.5/4.8           | 10  |
| CR32K6                | 6,602      | 2,410           | 12               | 11  | 6,602     | 2,420           | 9.3/4.7           | 11  |
| CR34K6                | 6,905      | 2,550           | 12               | 11  | 6,804     | 2,550           | --/4.6            | 11  |
| CR34KQ                | 7,157      | 2,840           | 15               | 10  | 7,157     | 2,840           | 9.6/4.9           | 10  |
| CR36K6                | 7,384      | 2,720           | 14               | 11  | 7,333     | 2,680           | --/4.9            | 11  |
| CR37KQ                | 7,862      | 3,180           | 16               | 10  | 7,837     | 2,990           | 10.4/5.7          | 10  |
| CR38K6                | 8,114      | 3,000           | 15               | 11  | 7,862     | 2,880           | 9.2/5.3           | 11  |
| CR41KQ                | 8,694      | 3,520           | 18               | 10  | 8,643     | 3,360           | 11.6/6.3          | 10  |
| CR42K6                | 8,870      | 3,240           | 15               | 11  | 8,769     | 3,240           | 10.2/5.9          | 11  |
| CR47KQ                | 10,281     | 4,020           | 20               | 10  | 10,206    | 4,030           | 15.2/7.1          | 10  |
| CR53KQ                |            |                 |                  |     | 11,264    | 4,500           | 17.9/8.2          | 10  |
| CR60K5                |            |                 |                  |     | 12,045    | 4,600           | 15.4/8.9          | 10  |
| CRN5-0500             |            |                 |                  |     | 14,490    | 4,970           | 17.5/10.1         | 10  |

| TEMPERATURA DE EVAPORACIÓN °F / °C | TEMPERATURA CONDENSACIÓN °F / °C | TEMPERATURA AMBIENTE °F / °C | TEMPERATURA DEL LÍQUIDO °F / °C | TEMPERATURA RETORNO °F / °C |
|------------------------------------|----------------------------------|------------------------------|---------------------------------|-----------------------------|
| 45 / 7.2                           | 130 / 54.4                       | 95 / 35.0                    | 115 / 46.11                     | 65 / 18.3                   |