



Datos de Rendimiento de Herméticos Para Aire Acondicionado - **R-22 - 60 Hz - KCAL**

Modelo	Monofásico				Trifásico			
	KCAL	VATIOS DE MOTOR	PFJ/T/Z AMPERIOS	EER	KCAL	VATIOS DE MOTOR	TF5/D(M) AMPERIOS	EER
<b>HERMÉTICOS R-22</b>								
CR16KQ	4,030	1,630	8.3	2.5				
CR16K6	4,110	1,540	6.9	2.7				
CR18KQ	4,610	1,870	8.3	2.5	4,540	1,810	5.6/2.8	2.5
CR18K6	4,540	1,700	7.6	2.7				
CR20KQ	4,990	1,980	8.9	2.5				
CR20K6	4,940	1,830	8.2	2.7				
CR22KQ	5,500	2,230	10.8	2.5				
CR22K6	5,570	2,040	9.2	2.7	5,440	1,990	6.0/3.0	2.7
CR24KQ	6,000	2,400	11.9	2.5	6,050	2,410	6.9/3.5	2.5
CR24K6	6,180	2,250	10	2.7	6,050	2,210	6.7/3.4	2.7
CR26K6	6,600	2,440	11.4	2.7				
CR28KQ	6,960	2,800	13.4	2.5	7,060	2,810	8.2/4.1	2.5
CR28K6	7,110	2,610	12.4	2.7	7,060	2,560	8.0/4.0	2.8
CR30KQ	7,510	2,990	14.2	2.5	7,560	3,010	--/4.3	2.5
CR30K6	7,560	2,750	12.9	2.7	7,510	2,710	8.3/4.2	2.8
CR32KQ	8,040	3,230	15.2	2.5	8,060	3,210	9.3/4.7	2.5
CR32K6	8,070	2,970	13.6	2.7	8,040	2,910	9.1/4.6	2.8
CR34K6	8,700	3,160	14.6	2.8				
CR34KQ	8,570	3,370	15.3	2.5	8,550	3,350	9.7/4.8	2.6
CR35K6	8,820	3,230	15.4	2.7	8,800	3,160	9.6/4.8	2.8
CR37KQ	9,280	3,640	17.4	2.5	9,180	3,500	10.2/5.1	2.6
CR38K6	9,630	3,520	17.2	2.7	9,550	3,440	10.5/5.3	2.8
CR41KQ	10,340	4,060	18.5	2.5	10,230	3,980	11.5/5.8	2.6
CR42K6	10,560	3,860	17.9	2.7	10,510	3,810	11.6/5.8	2.8
CR47KQ	11,970	4,580	21.5	2.6	11,900	4,540	13.7/6.9	2.6
CR53KQ	13,360	5,270	24	2.5	13,410	5,220	16.0/8.0	2.6
CR60K5	14,870	5,760	25.8	2.6	14,770	5,700	16.1/8.1	2.6
CRN5-0500	16,230	6,270	28	2.6	15,960	6,210	18.2/9.1	2.6

TEMPERATURA DE EVAPORACIÓN °F / °C	TEMPERATURA DE CONDENSACIÓN °F / °C	TEMPERATURA AMBIENTE °F / °C	TEMPERATURA DEL LÍQUIDO °F / °C	TEMPERATURA RETORNO °F / °C
45 / 7.2	130 / 54.4	95 / 35.0	115 / 46.11	65 / 18.3