



Datos de Rendimiento de Scroll Para Refrigeración - **HFC - 60 Hz - KCAL**

								Solamente Para Modelos ZF con Inyección Líquida		
Modelo	HP	°C Cond.	10°C	0°C	-5°C	-10°C	-15°C	-25°C	-30°C	-40°C
			50°F	32°F	23°F	14°F	5°F	-13°F	-22°F	-40°F
SCROLL PARA REFRIGERACIÓN 404A										
ZF06K4E ZS15K4E	2	35	8,340	6,050	5,090	4,260	3,450	2,340	1,920	1,210
		45	7,160	5,190	4,390	3,650	2,970	2,040	1,660	1,030
		55	5,900	4,260	3,600	3,020	2,470	1,740	1,440	910
ZF08K4E ZS19K4E	2.5	35	10,300	7,460	6,280	5,270	4,390	2,970	2,420	1,540
		45	8,820	6,400	5,390	4,510	3,780	2,570	2,090	1,340
		55	7,260	5,270	4,440	3,730	3,100	2,120	1,740	1,080
ZF09K4E ZS21K4E	3	35	11,400	8,290	6,980	5,850	4,910	3,350	2,720	1,740
		45	9,800	7,110	6,000	5,020	4,260	2,900	2,370	1,490
		55	8,060	5,850	4,940	4,130	3,480	2,390	1,940	1,240
ZF11K4E ZS26K4E	3.5	35	14,100	10,260	8,670	7,260	6,100	4,130	3,350	2,170
		45	12,200	8,850	7,460	6,250	5,240	3,550	2,900	1,870
		55	10,100	7,260	6,120	5,120	4,310	2,920	2,390	1,540
ZF13K4E ZS30K4E	4	35	15,300	11,800	10,100	8,520	7,230	4,910	3,960	2,390
		45	14,000	10,300	8,690	7,210	6,150	4,110	3,280	2,020
		55	11,800	8,340	6,930	5,720	4,890	3,300	2,720	1,940
ZF15K4E ZS38K4E	5	35	20,200	14,700	12,400	10,380	8,740	5,950	4,810	3,050
		45	17,400	12,600	10,600	8,870	7,510	5,090	4,130	2,600
		55	14,300	10,300	8,640	7,230	6,100	4,160	3,400	2,190
ZF18K4E ZS45K4E	6	35	20,400	14,600	12,300	10,300	8,690	5,870	4,790	3,050
		45	17,600	12,600	10,600	8,870	7,480	5,090	4,130	2,620
		55	14,400	10,300	8,690	7,260	6,150	4,210	3,450	2,170
ZF24K4E ZS56K4E	8	35	29,400	21,100	17,800	14,800	12,400	8,390	6,800	4,310
		45	25,200	18,100	15,200	12,800	10,700	7,310	5,950	3,730
		55	20,600	14,800	12,500	10,500	8,850	6,100	4,990	3,130
ZF33K4E ZS75K4E	10	35	35,000	28,800	25,200	21,500	17,800	12,100	9,800	6,140
		45	32,700	25,700	22,000	18,400	15,400	10,500	8,490	5,240
		55	28,200	21,300	18,000	14,900	12,700	8,740	7,130	4,410
ZF40K4E ZS92K4E	13	35	50,900	36,800	31,000	25,900	21,700	14,700	11,900	7,610
		45	43,600	31,600	26,600	22,300	18,700	12,800	10,400	6,530
		55	35,700	25,900	21,900	18,400	15,400	10,600	8,640	5,420
ZF48K4E ZS11M4E	15	35	59,000	42,500	36,000	30,000	24,930	16,880	13,700	8,750
		45	50,250	36,250	30,750	25,750	21,380	14,580	11,880	7,480
		55	40,750	29,250	24,850	20,880	17,400	12,030	9,830	6,130