



Selección de Voltaje de Scroll Para Refrigeración - 60 Hz

Modelo	Código del Motor	60 Hz Volts-Fase	Rangos de Amperaje			Capacitor de Marcha		
			RLA	LRA	MCC	MFD	Voltaje	Parte
ZF06/ZS15	PFV	208/230-1	13.6	61	19	40	370	014-0037-12
	TF5	200/230-3	9.3	55	13			
	TFD	460-3	4.3	27	6			
ZF08/ZS19	PFV	208/230-1	16.4	73	23	60	370	014-0037-36
	TF5	200/230-3	9.7	63	13.5			
	TFD	460-3	5	31	7			
ZF09/ZS21	PFV	208/230-1	16.4	88	23	50	370	014-0037-40
	TF5	200/230-3	11.1	77	15.5			
	TFD	460-3	5.7	39	8			
ZF11/ZS26	PFV	208/230-1	20.7	109	29	60	370	014-0037-37
	TF5	200/230-3	13.6	88	19			
	TFD	460-3	7.1	44	10			
ZF13/ZS30	PFV	208/230-1	26.8	129	37.5	60	370	014-0037-37
	TF5	200/230-3	15	99	21			
	TF7	380-3	8.2	57	11.5			
	TFD	460-3	8.2	50	11.5			
ZF15/ZS38	PFV	208/230-1	31.8	169	44.5	80	370	014-0037-38
	TF5	200/230-3	21.4	123	30			
	TF7	380-3	11.4	64	15.9			
	TFD	460-3	9.6	62	13.5			
ZF18/ZS45	TF5	200/230-3	23.9	156	33.5			
	TF7	380-3	12.6	70	17.7			
	TFD	460-3	9.3	70	13			
ZF24/ZS56	TWC	208/230-3	30.9	189	42			
	TW7	380-3	19.1	112	26			
	TWD	460-3	16.2	94	22			
ZF33/ZS75	TWC	208/230-3	44.9	278	61			
	TW7	380-3	24.6	151	33.5			
	TWD	460-3	21.7	127	29.5			
ZF40/ZS92	TWC	208/230-3	52.9	350	74			
	TW7	380-3	32	212	44.8			
	TWD	460-3	26.5	175	37			
ZF48/ZS11M	TWC	208/230-3	60	425	84			
	TW7	380-3	38.6	239	54			
	TWD	460-3	35	187	49			

Valor de amperaje sólo para operaciones de R404A. R-22 va a tener valor un poco más bajo

Selección de Voltaje de Scroll Para Refrigeración - **60 Hz Usando R-22**

Modelo	Código del Motor	60 Hz Volts-Fase	Rangos de Amperaje		
			RLA	LRA	MCC
ZB50KC	TF5	200/230-3	28.6	196	40
	TF7	380-3			
	TFD	460-3	14.2	100	20
ZB58KC	TF5	208/230-3	32.1	195	45
	TF7	380-3			
	TFD	460-3	16.4	95	23
ZB66KC	TF5	208/230-3	33.6	225	47
	TF7	380-3			
	TFD	460-3	17.3	114	24.2
ZB76KC	TF5	208/230-3	42	239	58
	TF7	380-3			
	TFD	460-3	19.2	125	26.9
ZB88KC	TF5	208/230-3			
	TF7	380-3			
	TFD	460-3	19.6	125	27.5

