

Especificaciones Mecánicas de Scroll Para Refrigeración

Modelo	Altura H mm	Diámetro D mm	Conexión		Conexión Rotalock		Puerto Inyección (ZF) ID (Pulg.)	Peso al Despacho kg.
			Succión DI (Pulg.)	Descarga DI (Pulg.)	Rosca de Succión	Rosca de Descarga		
SCROLL PARA REFRIGERACIÓN								
ZF06/ZS15	370	166	3/4	1/2	1 1/4	1	1/4	25.4
ZF08/ZS19	393	166	3/4	1/2	1 1/4	1	1/4	29.5
ZF09/ZS21	393	166	3/4	1/2	1 1/4	1	1/4	29.5
ZF11/ZS26	408	166	3/4	1/2	1 1/4	1	1/4	30.9
ZF13/ZS30	443	185	7/8	1/2	1 1/4	1	1/4	38.6
ZF15/ZS38	443	185	7/8	1/2	1 1/4	1	1/4	42.7
ZF18/ZS45	443	185	7/8	1/2	1 1/4	1	1/4	43.1
ZF24/ZS56	540	282	---	---	1-3/4	1-1/4	1/4	102
ZF33/ZS75	540	282	---	---	1-3/4	1-1/4	1/4	102
ZF40/ZS92	547	282	---	---	1-3/4	1-1/4	1/4	109
ZF48/ZS11M	593	282	---	---	2-2/4	1-3/4	1/4	119

Modelo	Altura H mm	Diámetro D mm	Conexión		Conexión Rotalock		Puerto Inyección (ZF) ID (Pulg.)	Peso al Despacho kg.
			Succión DI (Pulg.)	Descarga DI (Pulg.)	Rosca de Succión	Rosca de Descarga		
SCROLL DE REFRIGERACIÓN								
ZB50KC	478	240	1 1/8	7/8	1-3/4	1-1/4	N/A	59
ZB58KC	478	240	1 1/8	7/8	1-3/4	1-1/4	N/A	59.9
ZB66KC	533	240	1 3/8	7/8	1-3/4	1-1/4	N/A	60.3
ZB76KC	533	240	1 3/8	7/8	1-3/4	1-1/4	N/A	63.9
ZB88KC	533	240	1 3/8	7/8	1-3/4	1-1/4	N/A	63.9

